

EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1265/162/12/20/3034

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment:

Manufacturer: Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province

China

Description

PPE Type: protective glove against mechanical risks, cold risks

Product reference: LD6603

Article code : /

Glove description: 10 Gauge blue/black cut resistant terry brushed glove, with

sandy latex double dipped on palm and thumb, knitted wrist

Available sizes: 7/S-12/XXXL

Pictures:



SAFETY
Shuangdian Industrial Park C, Rudong
County, Jiangsu Province, China

LD6603

i

EN388 EN511



Size:9/L MM/YY 2X43D X1X

Reference standard:

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

EN 388:2016 + A1:2018

2 X 4 3 D

EN 511: 2006

X 1 X

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from DECEMBER, 2020

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by Didier GUISADO

MARKING

Certification and Quality Manager

Equipment and repealing the Directive 89/686/EEC.

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective

Date of first issue: 17 December 2020 End of validity date: 17 December 2025



www.ctcgroupe.com

cemarking@ctcgroupe.com



Nantong Jiadeli Safety Products Co., Ltd

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product : LD6603

Article code : /

Technical file index : 01

Last update : DECEMBER, 2020

IDENTIFICATION

Reference of the product: : LD6603

Article code: : /

Basic Model

Technical file index: : 01

Last update : : DECEMBER, 2020

Manufacturer:

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province

China

tel: +86 513 84610288 fax: +86 513 84618199

Factory:

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province

China

tel: +86 513 84610288 fax: +86 513 84618199

GLOVE DESCRIPTION

General glove description:

10 Gauge blue/black cut resistant terry brushed glove, with sandy latex double dipped on palm and thumb, knitted wrist

This glove is designed against mechanical risks, cold risks.

Type of coating finish: sandy

Visual description (picture back and palm sides):



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
			✓ Standard
§1	Requirements defined in the Annex II §1 are applicable to all PPE	7	✓ Instruction for use
			✓ Marking
	Manufacturer's instructions and information is available	7	Standard
§1.4			✓ Instruction for use
			Marking
§2.5	PPE which may be caught up during use	√	Standard Instruction for use
			Marking
		V	✓ Standard
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety		✓ Instruction for use
			✓ Marking
§2.14		V	√ Standard
	Multi-risk PPE		✓ Instruction for use
			✓ Marking
§3.3			✓ Standard
	The PPE is intended to protect against mechanical injuries	√	✓ Instruction for use
			✓ Marking
§3.7	Protection against cold	V	✓ Standard
			✓ Instruction for use
			✓ Marking

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm	double	black/blue	latex			0.5mm
Faiiii		blue/black	acrylic	400/g/m ²	10Gauges	
Back		blue/black	acrylic	400/g/m²	10Gauges	
Cuff		blue/black	acrylic/elastic	720/g/m²	10Gauges	
Binding		white/ red/ black/ blue/ orange/ yellow/ grey	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks, cold risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420:2020

Dexterity: 5

Available size range: 7/S-12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

- « X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
- « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	X
Tear strength resistance	4
Puncture resistance	3
Cut Resistance method (EN ISO 13997)	D
Impact Protection	-

The levels of performance have been measured on the palm

Cold hazard EN 511:2006

	Minimum performance level require	Performance obtained
Abrasion resistance	≥1	2
Tear strength	≥ 1	4
Flexibility behaviour for coated materials	no crack	conform
Extreme cold flexibility for glove resistant to -30°C	no crack	Χ
Convective cold	_	X
Contact cold	_	1
Water penetration	0 or 1	X

TEST REPORTS

Laboratory	CTC	Other
	S200100503_1 S200808355_1 S180912020_1 S190507210_1 S200302101_3(DMFu)	
EN 388	S200100503_1 S200302097_2	
EN 511	S200100503_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer:

Logo (€

Glove's reference: LD6603

Article Code: /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer:

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Method of marking on the glove :

Screen printng on the back of glove

Packaging:

12 pairs per poly bag,120 pairs per carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Cleaning:

The gloves are not washable.

MEANS OF CONTROL

ISO 9001 Certified, we do abrasion at CTC every year.



INSTRUCTION FOR USE

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province

China

Glove reference: LD6603

Article code: /

User notice index: 01

Last update : DECEMBER, 2020

SAFETY Shuangdian Industrial Park C, Rudong County, Jiangsu Province, China







Size:9/L MM/YY 2X43D X1X

Glove description:

10 Gauge blue/black cut resistant terry brushed glove, with sandy latex double dipped on palm and thumb, knitted wrist

This is a Personal Protective Equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018: innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)

4, rue Hermann Frenkel

69367 LYON Cedex 07

FRANCE

Applicable standards:

The glove meets the requirements of the standard EN ISO 21420: 2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available Size Range: 7/S-12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 2140 Annex B.

Moreover, this glove has been designed for the following applications:

- « X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Application :

Mechanical hazard - EN 388:2016 + A1:2018



2 X 4 3 D Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	X	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	3	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	D	(A to F)
Impact Protection		

<u>Application</u>: Cold risk - EN 511:2006



X1X Levels of performance

		_
Convective cold	Х	(on 4 maxi)
Contact cold	1	(on 4 maxi)
Water penetration	X	



Read carefully the instructions for use provided with the product

Protection limit:

This glove provides a protection for a limited contact time with cold items.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Contains natural rubber latex, which could cause allergic reactions, including anaphylactic choc.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

The performance levels can be reduced due to a level X of water penetration.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks mentioned are only valid for the palm of the glove (except Impact protection).

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity:

Available on : www.jdlsafety.com