EU-TYPE EXAMINATION CERTIFICATE



Certificate N° 0075/1265/162/12/18/3059

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer :

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province China

Description PPE Type : Product reference : Article code : Glove description :

protective glove against mechanical risks LRS3033 /

Available sizes :

Pictures :



Reference standard :

7 13 GAUGE SEAMLESS GLOVES WITH SMOOTH LATEX FULLY COATED AND SANDY LATEX COATED ON PALM AND THUMB, KNITTED WRIST. 7/S 8/M 9/L 10/XL 11/XXL





Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

2131X


« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from December 2018

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by Maxence DREVET Project Certification Manager





www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC. Nantong Jiadeli Safety Products Co., Ltd

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	LRS3033
Article code	:	Ι
Technical file index	:	01
Last update	:	December 2018

IDENTIFICATION

Reference of the product : Article code :	:	LRS3033 /
Basic Model		
Technical file index :	:	01
Last update :	:	December 2018

Manufacturer :

Nantong Jiadeli Safety Products Co., Ltd Shuangdian Industrial Park C, Rudong County, Jiangsu Province China tel : +86 513 84610288 fax : +86 513 84618199

Factory :

Nantong Jiadeli Safety Products Co., Ltd Shuangdian Industrial Park C, Rudong County, Jiangsu Province China tel: +86 513 84610288 fax: +86 513 84618199

GLOVE DESCRIPTION

General glove description :

13 GAUGE SEAMLESS GLOVES WITH SMOOTH LATEX FULLY COATED AND SANDY LATEX COATED ON PALM AND THUMB, KNITTED WRIST.

type of coating finish : sandy

Visual description (picture back and palm sides) :



Field of use

manufacturing industry

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	7	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§1.4	Manufacturer's instructions and information is available	7	 Standard ✓ Instruction for use Marking 	
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	7	Standard Instruction for use Marking	
§2.5	PPE which may be caught up during use	7	Standard Instruction for use	
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	7	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§3.3	The PPE is intended to protect against mechanical injuries	7	 ✓ Standard ✓ Instruction for use ✓ Marking 	

Available sizes :

Minimum length of glove (mm)	Sizes
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
		black	latex	800g/m2		0.8mm
Palm		orange	latex	560g/m2		0.5mm
		orange	nylon	300g/m2	13	
Back		orange	latex	560g/m2		0.5mm
		orange	nylon	300g/m2	13	
	thumb	black	latex	800g/m2		0.8mm
Cuff		orange / white	nylon / elastic	325g/m2	13	
Binding		white	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed for mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

5

Dexterity : Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	Х
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

TEST REPORTS

Laboratory	CTC	Other
	S180201132_1 SH60431-14 S180201676_1(DMFU)	
EN 388	S180201132_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer : Logo (€ Glove's reference : LRS3033 Article Code : / Size indicator Pictograms related to risks against which protection is offered with performance levels Information pictogram Address of Manufacturer : Date of Manufacture (month/year) and/or Serial number :

Marking example :



Method of marking on the glove :

screen printing on the back

Packaging :

12pairs per polybag, 120pairs per carton

PPE subject to ageing :

Peremption period : 12months when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.jdlsafety.com

MEANS OF CONTROL

1) ISO 9001 Certified

2) All inspection processes including sewing, moulding and all incoming raw materials are based on random acceptance sampling.

3) Goods Inwards Q.C. inspect and check all raw materials before releasing to Production Dept.

4) Production/Q.C. Dept. perform on-line checking on sewing machine floor for based on

EN420 sizing standard.

5) Q.C. Dept. perform size and label checks before forwarding to Moulding Dept.

6) Moulding/Q.C. Dept. will undertake final inspection tests for size, weight chemical testing and cutting/abrasion according to EN388 Standard each year.

7) Packaging checks are performed by Q.C. before shipment.

8) All reject materials are inspected and either disposed of responsibly or re-worked responsibly within the production process.



INSTRUCTION FOR USE

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County,Jiangsu Province China Glove reference : LRS3033 Article code: / User notice index : 01 Last update : December 2018 Available sizes : 7/S 8/M 9/L 10/XL 11/XX

Glove description :

13 GAUGE SEAMLESS GLOVES WITH SMOOTH LATEX FULLY COATED AND SANDY THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by : C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :

<u>Application</u> : Mechanical hazard - EN 388 : 2016



2 1 3 1 X Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	Х	(A to F)
Impact Protection		

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic choc. Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...). For gloves with different layers of material, the performance levels are warranted only for the whole glove. For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

Peremption period : 12months when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.jdlsafety.com