EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/1265/162/05/19/1490

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer :

Nantong Jiadeli Safety Products Co., Ltd Shuangdian Industrial Park C, Rudong County, Jiangsu Province China

Description PPE Type : Product reference : Article code : Glove description : Available sizes : Pictures :

protective glove against mechanical risks LY2019 /

13 GAUGE RED LINER COATED WITH BLACK LATEX GLOVE 6/XS 7/S 8/M 9/L 10/XL 11/XXL





Size:9/L MM/YY 2121X

Reference standard :

-

Levels of performance / class of protection

2121X

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from MAY 2019

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by Maxence DREVET Project Certification Manager

EN 420:2003+A1:2009

EN 388:2016

Date of first issue : 09 May 2019 End of validity date : 09 May 2024



Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726 Nantong Jiadeli Safety Products Co., Ltd

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

| Reference of the product | : | LY2019 |
|--------------------------|---|----------|
| Article code | : | 1 |
| Technical file index | : | 01 |
| Last update | : | MAY 2019 |

IDENTIFICATION

| Reference of the product : Article code : | : | LY2019 / |
|--|---|-------------|
| Basic Model | | |
| Technical file index : | : | 01 |
| Last update : | : | MAY 2019 |

Manufacturer :

Nantong Jiadeli Safety Products Co., Ltd Shuangdian Industrial Park C, Rudong County, Jiangsu Province China tel : +86 513 84610288 fax : +86 513 84618199

Factory :

Nantong Jiadeli Safety Products Co., Ltd Shuangdian Industrial Park C, Rudong County, Jiangsu Province China tel: +86 513 84610288 fax: +86 513 84618199

GLOVE DESCRIPTION

General glove description :

13 GAUGE RED LINER COATED WITH BLACK LATEX GLOVE type of coating finish : crinckle

Visual description (picture back and palm sides) :



Field of use

Craft trade, construction sector, trade fair construction, automotive industry, mechanical engineering industry, agricultural sector for mechanical risks (handling, DIY or tool use)

| Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation) | | | | |
|--|---|---|-----------------------|--|
| | | Applicable | Covered by | |
| | | | ✓ Standard | |
| §1 | §1 Requirements defined in the Annex II §1 are applicable to all PPE | \checkmark | ✓ Instruction for use | |
| | | | ✓ Marking | |
| | §1.4 Manufacturer's instructions and information is available | ~ | Standard | |
| §1.4 | | | ✓ Instruction for use | |
| | | | Marking | |
| | If it is known that the design performance of new PPE may be significantly | | Standard | |
| §2.4 | affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging. | | ✓ Instruction for use | |
| | | | | |
| | | | ✓ Marking | |
| | PPE which may be caught up during use | \checkmark | Standard | |
| §2.5 | | | ✓ Instruction for use | |
| | | | Marking | |
| §2.12 §3.3 | PPE bearing one or more identification markings or indicators directly or | Instruction for Instruction for Instruction for Instruction for Instruction for Instruction for Instruction for | | |
| | indirectly relating to health and safety | | | |
| | | | | |
| | The PPE is intended to protect against mechanical injuries | | | |
| | | | | |
| | | | ✓ Marking | |

Available sizes :

| Minimum length of glove (mm) | Sizes |
|------------------------------|--------|
| 220 | 6/XS |
| 230 | 7/S |
| 240 | 8/M |
| 250 | 9/L |
| 260 | 10/XL |
| 270 | 11/XXL |

Glove constitution :

| | Reference | Color | Material | Surfacic mass | Gauges | Thickness |
|---------|-----------|-------|-------------------|------------------|--------|-----------|
| Palm | | black | latex | 560g/m2 | | 1mm |
| Paim | | red | polyester | 200g/m2 | 13 | |
| Back | | red | polyester | 200g/m2 | 13 | |
| Cuff | | red | polyester/elastic | 300g/m2 | 13 | |
| Binding | | white | Polyester | | | |

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425. This glove is designed for against mechanical risks. It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

5

Dexterity :

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

| Protection offered | Performance levels |
|--------------------------------------|--------------------|
| Abrasion resistance | 2 |
| Blade cut resistance | 1 |
| Tear strength resistance | 2 |
| Puncture resistance | 1 |
| Cut Resistance method (EN ISO 13997) | Х |
| Impact Protection | - |

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

TEST REPORTS

| Laboratory | CTC | Other |
|------------|--|-------|
| | S181013211_1 S181115804_1 S180201676_1(DMFU) S180912020_1 | |
| EN 388 | S181013211_1 S181115804_1 | |

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer : Logo CC Glove's reference : LY2019 Article Code : / Size indicator Pictograms related to risks against which protection is offered with performance levels Information pictogram Address of Manufacturer : Date of Manufacture (month/year) and/or Serial number :

Marking example :



Method of marking on the glove :

screen printing on the back

Packaging :

12pairs per poly bag,120 pairs per carton

PPE subject to ageing :

Peremption period : 12months when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.jdlsafety.com

MEANS OF CONTROL

1) ISO 9001 Certified

2) All inspection processes including sewing, moulding and all incoming raw materials are based on random acceptance sampling.

3) Goods Inwards Q.C. inspect and check all raw materials before releasing to Production Dept.

4) Production/Q.C. Dept. perform on-line checking on sewing machine floor for based on EN420 sizing standard.

5) Q.C. Dept. perform size and label checks before forwarding to Moulding Dept.

6) Moulding/Q.C. Dept. will undertake final inspection tests for size, weight chemical testing and cutting/abrasion according to EN388 Standard.

7) Packaging checks are performed by Q.C. before shipment.

8) All reject materials are inspected and either disposed of responsibly or re-worked responsibly within the production process.



INSTRUCTION FOR USE

10/XL 11/XXL

Nantong Jiadeli Safety Products Co., Ltd

Shuangdian Industrial Park C, Rudong County, Jiangsu Province China Glove reference : LY2019

Article code:/User notice index :01Last update :MAY 2019Available sizes :6/XS7/S8/M

Biographic Street Stree

Size:9/L MM/YY 2121X

Glove description :

13 GAUGE RED LINER COATED WITH BLACK LATEX GLOVE

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

9/L

It has been subject to a UE-type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :

<u>Application</u> : Mechanical hazard - EN 388 : 2016



Levels of performance

| Abrasion resistance | 2 | (on 4 maxi) |
|--------------------------------------|---|-------------|
| Blade cut resistance | 1 | (on 5 maxi) |
| Tear resistance | 2 | (on 4 maxi) |
| Puncture resistance | 1 | (on 4 maxi) |
| Cut Resistance method (EN ISO 13997) | Х | (A to F) |
| Impact Protection | | |

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic choc.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

Peremption period : 12months when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

Declaration of conformity :

Available on : www.jdlsafety.com