



# EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

**Certificate N°**      **0075/1265/162/08/19/2463**

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

**Manufacturer :**      **Nantong Jiadeli Safety Products Co., Ltd**  
Shuangdian Industrial Park C, Rudong County, Jiangsu Province  
China

**Description**

**PPE Type :**      *protective glove against mechanical risks*

**Product reference :**      **N1594**

**Article code :**      **/**

**Glove description :**      **13 GAUGE POLYESTER GLOVES COATED WITH BLACK SMOOTH NITRILE ON PALM**

**Available sizes :**      **6/XS 7/S 8/M 9/L 10/XL 11/XXL 12/XXXL**

**Pictures :**



**Reference standard :**

**Levels of performance / class of protection**

**EN 420:2003+A1:2009**

-

**EN 388:2016**

**3 1 2 1 X**

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for use index 01 dated from August 2019

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

**Issued in Lyon by**   
**Didier GUISADO**  
Certification and Quality Manager

**Date of first issue :** 20 August 2019  
**End of validity date :** 20 August 2024



Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

[www.ctcgroupe.com](http://www.ctcgroupe.com)

[cemarking@ctcgroupe.com](mailto:cemarking@ctcgroupe.com)

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France  
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie  
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

**Nantong Jiadeli Safety Products Co., Ltd**

**MANUFACTURER'S TECHNICAL FILE TO THE  
PPE REGULATION 2016/425**

<b>Reference of the product</b>	<b>:</b>	<b>N1594</b>
<b>Article code</b>	<b>:</b>	<b>/</b>
<b>Technical file index</b>	<b>:</b>	<b>01</b>
<b>Last update</b>	<b>:</b>	<b>August 2019</b>

## IDENTIFICATION

Reference of the product :	:	N1594
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	August 2019

### **Manufacturer :**

Nantong Jiadeli Safety Products Co., Ltd  
Shuangdian Industrial Park C, Rudong County, Jiangsu Province  
China

tel : +86 513 84610288

fax : +86 513 84618199

### **Factory :**

Nantong Jiadeli Safety Products Co., Ltd  
Shuangdian Industrial Park C, Rudong County, Jiangsu Province  
China

tel: +86 513 84610288

fax: +86 513 84618199

## GLOVE DESCRIPTION

### General glove description :

13 GAUGE POLYESTER GLOVES COATED WITH BLACK SMOOTH NITRILE ON PALM  
type of coating finish : smooth

### Visual description (picture back and palm sides) :



### Field of use

construction sector, automotive industry, mechanical engineering industry, agricultural sector (e.g. handling, DIY or tool use)

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

### Available sizes :

Minimum length of glove (mm)	Sizes
220	6/XS
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL
280	12/XXXL

## **Glove constitution :**

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		black	nitrile	760g/m2		1mm
		grey	polyester	200g/m2	13	
Back		grey	polyester	200g/m2	13	
Cuff		grey	polyester/elastic	300g/m2	13	
Binding		blue/red	Polyester			

## **PROTECTION SCOPE**

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.  
This glove is designed for against mechanical risks.  
It is a category II product.

## **GENERAL REQUIREMENTS**

### **Standard EN 420 : 2003 + A1 : 2009**

Dexterity : 5

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

## **SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS**

### **Mechanical hazard EN 388 : 2016**

<b>Protection offered</b>	<b>Performance levels</b>
Abrasion resistance	3
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.


## TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	S181216109_1 S190100501_1 S180912020_1 S180201676_1(DMFU)	
EN 388	S181216109_1	

## MARKING - PACKAGING

### Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : N1594

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or Serial number :

### Marking example :



### Method of marking on the glove :

silk print, print on the back

### Packaging :

12 pairs per plastic bag, 120 pairs per carton

### PPE subject to ageing :

Peremption period : 12 months when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

### Declaration of conformity :

Available on : [www.jdlsafety.com](http://www.jdlsafety.com)

## MEANS OF CONTROL

- 1) ISO 9001 Certified
- 2) All inspection processes including sewing, moulding and all incoming raw materials are based on random acceptance sampling.
- 3) Goods Inwards Q.C. inspect and check all raw materials before releasing to Production Dept.
- 4) Production/Q.C. Dept. perform on-line checking on sewing machine floor for based on EN420 sizing standard.
- 5) Q.C. Dept. perform size and label checks before forwarding to Moulding Dept.
- 6) Moulding/Q.C. Dept. will undertake final inspection tests for size, weight chemical testing and cutting/abrasion according to EN388 Standard and send to CTC for test EN388,EN420..each year .
- 7) Packaging checks are performed by Q.C. before shipment.
- 8) All reject materials are inspected and either disposed of responsibly or re-worked responsibly within the production process.





## INSTRUCTION FOR USE

Nantong Jiadeli Safety Products Co., Ltd  
Shuangdian Industrial Park C, Rudong County, Jiangsu Province  
China

Glove reference : N1594  
Article code: /  
User notice index : 01  
Last Update : August 2019  
Available sizes : 6/XS 7/S 8/M 9/L 10/XL 11/XXL 12/XXXL



### Glove description :

13 GAUGE POLYESTER GLOVES COATED WITH BLACK SMOOTH NITRILE ON PALM

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)  
4, rue Hermann Frenkel  
69367 LYON Cedex 07  
FRANCE

### Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

#### Application :

Mechanical hazard - EN 388 : 2016



3 1 2 1 X  
Levels of performance

Abrasion resistance	3	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

### Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

### Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

### PPE subject to ageing :

Peremption period : 12 months when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

### Declaration of conformity :

Available on : [www.jdlsafety.com](http://www.jdlsafety.com)