

3F, Building Block 2, No. 3400 Gonghexin Road,

Jing'an District - Shanghai 200436, P.R. CHINA

E-mail: ctcshanghai@ctcgroupe.com





中国认可 国际互认 检测 TESTING **CNAS L4577**

TEST REPORT

Page 1/3

上海市静安区共和新路3400号2幢3层 Tél.: +86 21 68 55 50 32 Report No.: S230402667_1 Fax: +86 21 68 55 50 33

06 April 2023

APPLICANT: NANTONG JIADELI SAFETY PRODUCTS CO.

LTD 南通嘉得利 (C00498)

SHUANGDIAN INDUSTRIAL PARK C RUDONG

226400 RUDONG JIANGSU

CHINA

Date of receipt

:03 Apr. 2023

Testing period

:06 Apr. 2023

:06 Apr. 2023

Buyer: --

Service

21 gauge b. comb knitted grey cut resistant shell with black palm dipped PU coating glove

Style / Article no. :PD6867

hr-sh@jdlsafety.com

ronnie.gu@jdlsafety.com

Test(s) requested

Sample description:

For CE Marking: Yes

Previous report

Brand / Section

: REGULAR

Product category Product type

Season

:FIRST TEST Test stage

End use Factory name

Supplier name Exported to

Factory code

1. Conclusion:

	<u>Tests description</u>	<u>Conformity</u>
	ANSI-ISEA 105: 2016	
1	Cutting resistance TDM	Level A3

Fail: requirements not met None: no requirement for this test N/A: not applicable

Approved by

Henry YAN 严滨

Laboratory Manager







TEST REPORT

Page 2/3

Report No.: S230402667_1

06 April 2023

APPLICANT: NANTONG JIADELI SAFETY PRODUCTS CO.

LTD 南通嘉得利 (C00498)

2. Sample(s) description assigned by laboratory:

Size	Analyzed product	<u>Description</u>	Sample information
	GLOVE		
		palm	



230402667







TEST REPORT

Page 3/3

Report No.: S230402667_1

06 April 2023

APPLICANT: NANTONG JIADELI SAFETY PRODUCTS CO.

LTD 南通嘉得利 (C00498)

3. GLOVE/

palm

	Method	Client Requirement	Unit	Result	Conformity
(+) 5.1.1. Cutting resistance TDM	ASTM F2992 /F2992M - 15				
Correction factor of the sharp edge of the blade with the neoprene				0.93	
Load for a distance of 20 mm cut			g	1400	
Performance level				Level A3	

END OF TEST REPORT

(+)CNAS accreditation

Unless otherwise specified, the physical test items in this report performed in CTC Shanghai lab were conditioned and tested in the environment of T $23\pm2^{\circ}$ C / RH $50\pm4\%$.

Performance level 0 means the glove falls below the minimum performance level for the given individual hazard

Classification Table for Cut Resistance (ANSI-ISEA 105)

(======================================					
Level	Weight (grams) needed to cut through material with 20 mm of blade travel				
A1	>=200				
A2	>=500				
A3	>=1000				
A4	>=1500				
A5	>=2200				
A6	>=3000				
A7	>=4000				
A8	>=5000				
A9	>=6000				

The report is issued by CTC Shanghai under its General Conditions printed overleaf. The results shown in this report refer only to the sample (s) tested Except by special arrangement, the test items will not be retained by CTC Shanghai for more than 3 months. The test report shall not be reproduced, except in full, without the written approval of the testing laboratory.